

AD

RSIC-588

LIGHT REFLECTION FROM ROUGH SURFACES

by
V. K. Polyanskiy
V. P. Rvachev

Optika i Spektroskopiya, 20, No. 4, 701-708 (1966)

Translated from the Russian

September 1966

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

REDSTONE SCIENTIFIC INFORMATION CENTER

REDSTONE ARSENAL, ALABAMA

JOINTLY SUPPORTED BY



U.S. ARMY MISSILE COMMAND



GEORGE C. MARSHALL SPACE FLIGHT CENTER

GPO PRICE \$ _____

CFSTI PRICE(S) \$ _____

Hard copy (HC) \$1.00

Microfiche (MF) 1.50

LIGHT REFLECTION FROM ROUGH SURFACES

by
V. K. Polyanskiy
V. P. Rvachev

Optika i Spektroskopiya, 20, No. 4, 701-708 (1966)

Translated from the Russian

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Translation Branch
Redstone Scientific Information Center
Research and Development Directorate
U. S. Army Missile Command
Redstone Arsenal, Alabama 35809

The effect of the scattering of polarized light by a dull dielectric surface has been studied. The zeroth diffraction approximation proves to be more detailed than does the ray-optics approximation. In such an approximation, we must repeatedly explain the fact of light depolarization and the dependence of polarization effects upon the scattering conditions and also the displacement of the maximum of the scattering curve for larger observation angles.

AUTHOR


There are at present two methods for studying the interaction of light with a rough interface between two media. The first (stricter) consists of mathematically studying the diffraction of plane waves by a rough interface. Using this method, Rayleigh (V. Strutt)¹ gave an approximate solution to the problem of plane-wave scattering by a sinusoidal surface for normal incidence. Later on, a method was developed by Andronov and Leontovich² and Antokol'skiy³; finally, articles by Brekhovskikh⁴ described a solution to the problem of plane-wave scattering by a periodic surface for arbitrary angles of incidence, and gave the results of specific calculations for a sinusoidal and broken periodic (sawtooth) surface. Another method uses the fact that a rough surface can be represented as a set of microareas statistically distributed with respect to orientation, each of which reflects according to the laws of ray optics⁵. These representations are a basis for articles by Gershun and Popov⁶, Ivanov and Toporets⁷, Mullamaa⁸, Gorodinskiy⁹, and a number of others.

We should note that these two methods for solving a particular problem coincide at a very small number of points and are, in essence, developed independently. Of particular importance is an article by Isakovich¹⁰ which is devoted to the problem of wave scattering by a totally reflecting statistically-rough surface. This is the main point of an article which is quite familiar to us which notes the tendency of two methods of investigating the optical properties of dull surfaces to converge.

The purpose of this article is to study the scattering properties of dull surfaces in polarized light and to explain some observed effects using light-diffraction representations in addition to those of ray optics. Here, we will restrict ourselves to considering the effects at the interface of isotropic transparent media.

1. The experimental device intended for measuring brightness is similar to the one described by Gershun and Popov⁶ but has in addition

an interference light filter, polarizer, and analyzer. The FEU-19 photomultiplier is used to receive radiation; the signal generated by the photomultiplier is sent to the reference unit UF-206. The optical systems of the illuminator and receiver make it possible to assign aperture angles of 2° to $12'$ for the illuminating and recorded beams; this corresponds to the minimum solid angle $\omega = 1 \cdot 10^{-6}$ ster. In order to provide appropriate light fluxes, a high-power heater tube (K-30, 17 v, 170 w) was used as the light source, and was enclosed by a jacket cooled by circulating water. An interference light filter $\lambda = 550$ nm was used to monochromatize the light. The error in reading the orientations of the principal planes of the polarizer and analyzer did not exceed $20'$; the error in reading the angles of incidence or observation was $10'$, while the sums of these angles were $2'$. The specimens were placed on the stand of a goniometric circle. Figure 1 gives the principle of this device.



- | | |
|---|---|
| 1 - Aperture Diaphragm
of Illuminator | 6 - Field Diaphragm |
| 2 - Interference Light Filter
(550 nm) | 7 - Aperture Diaphragm
of Receiver |
| 3 - Polarizer | 8 - Photomultiplier |
| 4 - Object | 9 - Reference Device |
| 5 - Analyzer | (Total Length of Optical
System 2.3 m) |

Figure 1. Optical Diagram of Device.

2. Experimental Basis. We shall consider a rough surface as being a set of statistically distributed microareas. We shall assume the incident light beam is parallel, monochromatic, and linearly polarized. The state of polarization of this beam will be described by the azimuthal angle ϕ between the direction of oscillation of the electric

vector and the plane of incidence. Observations will be made in a plane coinciding with the plane of incidence; the angles of incidence β and observation α are read off relative to the normal to the surface. The index of refraction n of the second medium relative to the first is assumed to be real and greater than unity. In accordance with the ray-optics approximation we shall assume that rays reflected from microareas oriented uniquely will propagate in every given direction. The normals of the microareas under consideration lie in the plane of incidence. The orientation of each microarea is determined by the angle γ between the normal to the surface and the normal to the microarea.

In the ray-optics approximation the effect of a set of identically oriented microareas is equivalent to the effect of one area having a corresponding magnitude and orientation. Rays reflected by different microareas are, in general, not coherent; the total intensity of the beam reflected in a given direction is determined as a sum of partial intensities.

If we assume that the reflected beam consists of a set of singly-reflected rays (i. e., multiple reflections are not considered), then, as in the case of a polished surface, the reflected beam is plane-polarized but the plane of polarization is turned so that the azimuthal angle φ' between the plane of oscillation of the electric vector and the plane of observation is determined by the relationship

$$\operatorname{tg} \varphi' = - \frac{\cos \left(\frac{\alpha + \beta}{2} - r \right)}{\cos \left(\frac{\alpha + \beta}{2} + r \right)} \operatorname{tg} \varphi, \quad (1)$$

where r (angle of refraction) is determined by the Snell law $\sin(\alpha + \beta)/2 = n \sin r$. In order to obtain (1) we must expand the electric vector in the incident beam into s- and p-components, use the Fresnel formulas for each of them, and find the ratio of these components in the reflected beam. We must set $\alpha = \beta$ for a polished surface.

If we let $\varphi = 45^\circ$ in the incident beam, then the s- and p-components of the electric vector in the incident beam are the same; in this sense, the incident plane-polarized beam is equivalent to a beam of ordinary (unpolarized) light. Measurements using different types of analyzers corresponding to the transmission of electric vectors with azimuths $0, \pi/2, \varphi', \varphi' \pm \pi/2$, all other conditions being equal, make it possible to obtain information as to the changes both ordinary beams and polarized beams undergo upon reflection. Thus, from the first pair of readings N_0 and $N_{\pi/2}$ (in view of the above-stipulated inherent equivalence

of the incident plane-polarized flux with azimuth $\Phi = 45^\circ$ owing to the fact that the p- and s-components of the electric vector are equivalent) we obtain

$$P = \frac{N_0 - N_{\pi/2}}{N_0 + N_{\pi/2}}$$

for the degree of polarization of ordinary light when reflected from the surface under consideration. If the reflected beam is completely polarized the reading $N_{\Phi' \pm \pi/2}$ is zero. Since the beam is partially depolarized after reflection, $N_{\Phi' \pm \pi/2} \neq 0$. The degree of depolarization will be computed from the relationship

$$\Delta = 1 - \frac{N_{\Phi'} - N_{\Phi' \pm \pi/2}}{N_{\Phi'} + N_{\Phi' \pm \pi/2}} = \frac{2N_{\Phi' \pm \pi/2}}{N_{\Phi'} + N_{\Phi' \pm \pi/2}} = \frac{2N_{\min}}{N_{\min} + N_{\max}}$$

The quantities P and Δ characterize the changes in beams of different types (ordinary and polarized) although the incident beams are plane-polarized in both cases. Under the above assumptions, it is not difficult to obtain the relationship

$$P = \frac{\cos^2 \left(\frac{\alpha + \beta}{2} + r \right) - \cos^2 \left(\frac{\alpha + \beta}{2} - r \right)}{\cos^2 \left(\frac{\alpha + \beta}{2} + r \right) + \cos^2 \left(\frac{\alpha + \beta}{2} - r \right)} = \frac{1 - \operatorname{tg}^2 \Phi'}{1 + \operatorname{tg}^2 \Phi'} \quad (2)$$

for the degree of polarization.

This assumption must be satisfied in the same manner as in the assumption that the outer component of the reflected flux maintains the state of polarization of the incident flux¹¹. In this case $\Delta = 0$.

3. Experimental Results. The selection of the object for experimental study was determined by the requirements that the inner component be absent, and that there be no ellipticity in the reflected beam. In other words, the object must only have an outer component and possess a real index of refraction. For this purpose, a plate of black glass with refractive index $n = 1.515$ was chosen (determined according to the Brewster angle) where one surface was polished and the other dulled mechanically (electrocorundum No. 240). By experimentally studying the structure and curve of brightness of the beam reflected by the polished surface of the specimen, we established that the imposed requirements are satisfied within the limits of experimental error.

This agrees with Gorodinskiy's data⁹. In a beam mirror reflected by the polished surface the light becomes completely polarized and the orientation of the electric vector corresponds to expression (1). Relationship (2) is also well satisfied.

Figures 2 and 3, which give typical experimental curves, characterize the results of investigating the polarization characteristics of beams reflected from a dull surface.




Figure 2. Degree of Polarization of a Light Beam Reflected from a Dull Surface.

The results given in Figure 2 are also found to agree with Gorodinskiy's results⁹ obtained in experiments using ordinary light. Our curves permit us to conclude that light polarization, upon reflection from a dull surface, depends considerably upon the angle of incidence β . When β decreases, the degree of polarization has a smaller maximum and the maximum is displaced in the direction of lower values for the half-sums of the angles of incidence and observation $(\alpha + \beta)/2$. When $(\alpha + \beta)/2$ is fixed and less than or about equal to 45° , polarization increases with a decrease in β ; if $(\alpha + \beta)/2 \geq 45^\circ$, polarization decreases when β decreases.

The results given in Figure 3 characterize depolarization caused by reflection from a dull surface. Here, the polarization properties as a function of the angle of incidence prove to be much more clearly




Figure 3. Depolarization of a Light Beam Upon Reflection from a Dull Surface.

defined. For small angles of incidence the polarization is relatively low but increases rapidly when the angle of observation increases. For large angles of incidence the polarization is great and decreases rapidly when the angle of observation increases. When $\beta = 45^\circ$ the depolarization was almost constant for our experiment when the angle of observation changed.

As was the case for reflection from a dull surface, the electric-vector orientation predominating in a beam reflected from a dull surface is determined so accurately from Equation (1) that the measured angles are no different from those computed. Equation (2) which is very accurate for beams reflected from a dull surface yielded somewhat exaggerated results for this dull surface; the greater the surface roughness and the smaller the angle of incidence, the greater the deviation of the results from those calculated. The assumption as to the state of polarization remaining constant upon reflection is only weakly satisfied and the magnitude of the depolarized flux can prove greater than the polarized one.

4. Discussion of Experimental Results. The idea of representing the diffusion-reflected beam as a set of parallel beams mirror-reflected from microareas makes it possible to obtain satisfactory results when the polarization plane is rotated for reflection of a plane-polarized beam; it also makes it possible, at least qualitatively, to form an opinion as to the distribution function of the microareas with respect to direction^{7,8}.


The presence of a depolarized component in the beam and its low (in comparison to that computed using the Fresnel formulas) polarization upon reflection from a dull surface is usually associated with the presence of rays which are reflected more than once. However, this explanation is not sufficient since, proceeding only from the ray-optics representations, we are often unable to explain such experimental facts as the deflection in the intensity maximum from the direction of mirror reflection toward larger angles of observation, the relatively high depolarization component in the reflected beam, and also a number of other effects. Thus, in order to explain the fact that the polarized and depolarized fluxes are roughly equivalent, we must assume on the basis of the concept of multiple reflection that the number of times multiple reflection occurs is at least 20-25 times greater than the number of times single reflection occurs. (For every reflection from the glass surface, which possesses, as is known, a reflection coefficient of the order of 4-5% and for equal angles of incidence and reflection ($\leq 50^\circ$) the beam must attenuate by a factor of 20-25.) However, such an assumption contradicts Gershun's data⁶ which deals with the distribution function of the direction of the microareas.

The effects which are observed when light is reflected from a dull surface can be explained in greater detail if we use diffraction representations (even when we restrict ourselves to the zeroth diffraction approximation).

Let us consider the interaction of a plane wave and an aperiodic uniform reflecting lattice. In other words, for the sake of simplicity, we shall assume that the dull surface consists of a set of plane bands with parallel adjacent edges. The bands are of different widths l and are tilted differently. The inclination of the bands is given by the angle γ . The bands under consideration are similar to the microareas; qualitatively, such a simplification for the object does not affect the results (however, it is necessary to introduce a correction (the form factor) for quantitative calculations). Figure 4, which shows one such band, also gives the notation which will be necessary below.

The intensity distribution in the diffraction pattern is determined by the path difference δ . Upon using ordinary methods to compute the path difference, we obtain, in our case,

$$\delta = 2l \cos \frac{\alpha + \beta}{2} \sin \left(\frac{\alpha - \beta}{2} - \gamma \right) . \quad (3)$$



β - Angle of Incidence α_0 - Direction of Principal Maximum
 α - Angle of Observation Path Difference $\delta = AD - AC$

Figure 4. Calculation of Reflection Allowing for Diffraction Effects.

The path difference $\delta = 0$ for the direction of the principal (zeroth) diffraction maximum. It is clear from Figure 4 that this occurs when $\alpha_0 = \beta + 2\gamma$ which is the same as the mirror-reflection condition.

Relationship (3) shows that the direction of the zeroth diffraction maxima, created by each individual microarea (principal part of the curve) is determined only by their orientation, i. e., the direction distribution function^{5,6,7} $f(\gamma)$. The direction of propagation of the maxima of the first and higher orders is determined not only by the direction distribution function but also by the size distribution function.

In contrast to the ray-optics approximation the principal diffraction maximum proves to be blurred. Using relationship (3) to estimate the diffraction broadening of the reflected microarea of the pencil of rays allowing for the fact that the direction to the first minimum is determined by the condition $\delta = \lambda$ we arrive at the result

$$\Delta \alpha \geq \frac{\lambda}{2l}, \quad (4)$$

where broadening increases with an increase in the angle of incidence β and the angle of inclination of the microarea γ .

In the case of oblique incidence the diffraction pattern proves to be asymmetric. In particular, the intensity distribution in the principle maximum (better termed principal beam) also proves to be asymmetric.

In fact, let us determine the directions $\alpha_0 + 2\psi$ and $\alpha_0 - 2\xi$ for which the path difference is the same in absolute value and opposite in sign. As is not difficult to see, the corresponding conditions can be written on the basis of (3) in the form

$$\cos\left(\frac{\alpha_0 + \beta}{2} + \psi\right) \sin \psi = \cos\left(\frac{\alpha_0 + \beta}{2} - |\xi|\right) \sin |\xi|. \quad (5)$$

We can easily verify that the last equality is satisfied by nonzero values of ψ and ξ only when

$$|\psi| > |\xi|. \quad (6)$$

Since the intensity in a given direction is determined (for ordinary light) by the path difference, we can conclude on the basis of relationships (5) and (6) that within the limits of each diffraction maximum when the angle of observation increases the intensity first increases rapidly (from zero to some maximum) and then drops more slowly to zero. If the maximum under consideration is represented in the form of a fringe on the band pattern, the fringe proves to be asymmetric -- turned in the direction of increasing angles of observation read off from the normal. (Note in passing that this statement also refers to the form of the spectral line found in diffraction spectral devices for oblique incidence.) Asymmetry in the principal beams leads to asymmetry in the curve. In fact, if two principal beams (two principal maxima) caused by diffraction from different microareas partially intersect, then assuming these beams are mutually incoherent, the total intensity is calculated as the sum of the intensities in each beam:

$$I(\alpha) = I_1(\alpha) + I_2(\alpha).$$

In such a case, the position of the resulting maximum is determined by the condition (Figure 5):

$$\frac{d}{d\alpha} I_1(\alpha) = - \frac{d}{d\alpha} I_2(\alpha).$$

By extending such a consideration to an arbitrary number of beams we are led to the conclusion that the maximum of reflection must be shifted in the direction of larger angles of observation for oblique illumination of a dull glass. This was also observed experimentally. Note that such a shift in the maximum invariably leads to error in determining the distribution function of the microareas by familiar methods^{7,8}.




Figure 5. Illustration of the Shift in Maximum for Addition of Asymmetric Pulses.

If the incident beam is plane-polarized, it is natural to assume that a beam reflected from one microarea is polarized and characterized by the azimuth φ' in Equation (1).

If rays reflected from microareas uniquely propagate in a direction determined by the angle of observation α and irradiation and observation are performed using strictly parallel beams, then, assuming there is no multiple reflection, the reflected beam becomes plane-polarized with varying azimuth.

The presence of multiple reflection involves some depolarization; however, the intensity contributed by multiple reflection can barely exceed 3-5% of the total flux.

The depolarization resulting from the finite dimensions of the angular aperture of the receiver system and illuminator system is negligibly small under our conditions since (see Section 1) the aperture angles lie within the limits of $12'$ - $15'$ (the diameters of the diaphragms of the collimator and receiver are 0.8 mm and the focal lengths of the objectives are 300 mm).

In fact, the principal beams resulting from diffraction on the microareas with different orientations are propagated in the direction of observation. These beams are incoherent and are polarized in different planes. (For normal incidence on the microarea, the reflected beam retains the azimuth of the incident beam (45°); when the angle of incidence is very close to the Brewster angle the azimuth is 90° ; for further increase, the azimuthal angle reaches 135° .)

When the dimensions of the microareas are comparable with the wavelength of light we may find a good deal of beam overlapping. Thus, if $l \cos (\beta + \alpha) / 2 \approx 5\lambda$ then in accordance with (3), the principal beams from the microareas propagate in the direction of observation and the normal to the microarea lies within the limits of 12° . The effect of beam overlapping is, in general, equivalent to an increase in the aperture of the observer system; therefore, it is an unnecessary precaution to attempt to reduce the aperture angle of the latter to less than 1° . Overlapping of the principal beams occurring as a result of diffraction on the microareas with different orientation and therefore characterized by different azimuths must lead to a partial depolarization of the resultant beam. This effect has also been observed experimentally.

Beam overlapping must be reduced when the effective dimensions of the microareas are increased, i. e., when the first factor in expression (3), $l \cos (\alpha + \beta) / 2$, is larger or when the angle of incidence β is smaller. When there is little beam overlapping (diffraction maxima from different microareas) there is little depolarization. When β increases depolarization must increase. This effect has been observed experimentally and is shown in Figure 3 (for small α). An increase in the angle of incidence and a decrease in l results in conditions where the dull surface begins to introduce a mirror component^{12,13}. In this case depolarization decreases with an increase in β . The appearance of this mirror effect can be explained by the features of the curves in Figure 3 for larger values of β and α . Under certain conditions, these effects compensate for one another; in our case this occurs when $\beta = 45^\circ$.

A reduction in the dimensions of the surface microstructure (processing with finer abrasives) is accompanied by the appearance of partial coherence which leads to a reduction in surface depolarization and, in the long run, to mirror (coherent) reflection. The laws described by Gorodinskiy⁹ explain this.

Thus, we can say that depolarization, upon reflection, is due not only to the presence of multiple reflection and finite aperture of the observer device but also (mainly) to diffraction by the surface microareas.

LITERATURE CITED

1. V. Strutt (Rayleigh), Teoriya zvuka (Theory of Sound), Pub. by AS USSR, Vol. II, Moscow, 1954.
2. A. A. Andronov, M. A. Leontovich, ZhRfKhO, 38, 485, 1926.
3. M. L. Antokol'skiy, DAN SSSR (Reports of the Acad. Sci., USSR), 62, 203, 1948.
4. L. M. Brekhovskikh, ZhETF (Journal of Experimental and Theoretical Physics), 23, 275, 289, 1952.
5. P. Bougner, Opticheskiy traktat o gradatsii sveta (Optical Treatise on Light Gradation), Pub. by AS USSR, Moscow, 1950.
6. A. A. Gershun, O. I. Popov, Transactions of the GOI (State Optical Institute) 24, No. 143, 3, 1955.
7. A. P. Ivanov, A. S. Toporets, ZhTF (Journal of Technical Physics), 26, 623, 631, 1956.
8. Yu. Mullamaa, Issled. po fizike atmosf. (Study of Atmospheric Physics), AS ESSR, 3, 5, 1962.
9. G. M. Gorodinskiy, Opt. i spektr. (Optics and Spectroscopy), 16, 112, 1964.
10. I. A. Isakovich, ZhETF, 23, 305, 1952.
11. A. S. Toporets, ZhETF, 20, 390, 1950.
12. A. S. Toporets, Opt. i spektr., 16, 102, 1964.
13. G. S. Landsberg, Optika (Optics), GTI, Moscow, 1957.

DISTRIBUTION

	No. of Copies		No. of Copies
<u>EXTERNAL</u>		U. S. Atomic Energy Commission	1
Air University Library	1	ATTN: Reports Library, Room G-017	
ATTN: AUL3T		Washington, D. C. 20545	
Maxwell Air Force Base, Alabama 36112		U. S. Naval Research Laboratory	1
U. S. Army Electronics Proving Ground	1	ATTN: Code 2027	
ATTN: Technical Library		Washington, D. C. 20390	
Fort Huachuca, Arizona		Weapons Systems Evaluation Group	1
U. S. Naval Ordnance Test Station	1	Washington, D. C. 20305	
ATTN: Technical Library, Code 753		John F. Kennedy Space Center, NASA	2
China Lake, California 93555		ATTN: KSC Library, Documents Section	
U. S. Naval Ordnance Laboratory	1	Kennedy Space Center, Florida 32899	
ATTN: Library		APGC (PGBPS-12)	1
Corona, California 91720		Eglin Air Force Base, Florida 32542	
Lawrence Radiation Laboratory	1	U. S. Army CDC Infantry Agency	1
ATTN: Technical Information Division		Fort Benning, Georgia 31905	
P. O. Box 808		Argonne National Laboratory	1
Livermore, California		ATTN: Report Section	
Sandia Corporation	1	9700 South Cass Avenue	
ATTN: Technical Library		Argonne, Illinois 60440	
P. O. Box 969		U. S. Army Weapons Command	1
Livermore, California 94551		ATTN: AMSWE-RDR	
U. S. Naval Postgraduate School	1	Rock Island, Illinois 61201	
ATTN: Library		Rock Island Arsenal	1
Monterey, California 93940		ATTN: SWERI-RDI	
Electronic Warfare Laboratory, USAECOM	1	Rock Island, Illinois 61201	
Post Office Box 205		U. S. Army Cmd. & General Staff College	1
Mountain View, California 94042		ATTN: Acquisitions, Library Division	
Jet Propulsion Laboratory	2	Fort Leavenworth, Kansas 66027	
ATTN: Library (TDS)		Combined Arms Group, USACDC	1
4800 Oak Grove Drive		ATTN: Op. Res., P and P Div.	
Pasadena, California 91103		Fort Leavenworth, Kansas 66027	
U. S. Naval Missile Center	1	U. S. Army CDC Armor Agency	1
ATTN: Technical Library, Code N3022		Fort Knox, Kentucky 40121	
Point Mugu, California		Michoud Assembly Facility, NASA	1
U. S. Army Air Defense Command	1	ATTN: Library, I-MICH-OSD	
ATTN: ADSX		P. O. Box 29300	
Ent Air Force Base, Colorado 80912		New Orleans, Louisiana 70129	
Central Intelligence Agency	4	Aberdeen Proving Ground	1
ATTN: OCR/DD-Standard Distribution		ATTN: Technical Library, Bldg. 313	
Washington, D. C. 20505		Aberdeen Proving Ground, Maryland 21005	
Harry Diamond Laboratories	1	NASA Sci. & Tech. Information Facility	5
ATTN: Library		ATTN: Acquisitions Branch (S-AK/DL)	
Washington, D. C. 20438		P. O. Box 33	
Scientific & Tech. Information Div., NASA	1	College Park, Maryland 20740	
ATTN: ATS		U. S. Army Edgewood Arsenal	1
Washington, D. C. 20546		ATTN: Librarian, Tech. Info. Div.	
		Edgewood Arsenal, Maryland 21010	

	No. of Copies		No. of Copies
National Security Agency ATTN: C3/TDL Fort Meade, Maryland 20755	1	Brookhaven National Laboratory Technical Information Division ATTN: Classified Documents Group Upton, Long Island, New York	1
Goddard Space Flight Center, NASA ATTN: Library, Documents Section Greenbelt, Maryland 20771	1	Watervliet Arsenal ATTN: SWEWV-RD Watervliet, New York 12189	1
U. S. Naval Propellant Plant ATTN: Technical Library Indian Head, Maryland 20640	1	U. S. Army Research Office (ARO-D) ATTN: CRD-AA-IP Box CM, Duke Station Durham, North Carolina	1
U. S. Naval Ordnance Laboratory ATTN: Librarian, Eva Liberman Silver Spring, Maryland 20910	1	Lewis Research Center, NASA ATTN: Library 21000 Brookpark Road Cleveland, Ohio 44135	1
Air Force Cambridge Research Labs. L. G. Hanscom Field ATTN: CRMCLR/Stop 29 Bedford, Massachusetts 01730	1	Systems Engineering Group (RTD) ATTN: SEPIR Wright-Patterson Air Force Base, Ohio 45433	1
Springfield Armory ATTN: SWESP-RE Springfield, Massachusetts 01101	1	U. S. Army Artillery & Missile School ATTN: Guided Missile Department Fort Sill, Oklahoma 73503	1
U. S. Army Materials Research Agency ATTN: AMXMR-ATL Watertown, Massachusetts 02172	1	U. S. Army CDC Artillery Agency ATTN: Library Fort Sill, Oklahoma 73504	1
Strategic Air Command (OAI) Offutt Air Force Base, Nebraska 68113	1	U. S. Army War College ATTN: Library Carlisle Barracks, Pennsylvania 17013	1
Picatinny Arsenal, USAMUCOM ATTN: SMUPA-VA6 Dover, New Jersey 07801	1	U. S. Naval Air Development Center ATTN: Technical Library Johnsville, Warminster, Pennsylvania 18974	1
U. S. Army Electronics Command ATTN: AMSEL-CB Fort Monmouth, New Jersey 07703	1	Frankford Arsenal ATTN: C-2500-Library Philadelphia, Pennsylvania 19137	1
Sandia Corporation ATTN: Technical Library P. O. Box 5800 Albuquerque, New Mexico 87115	1	Div. of Technical Information Ext., USAEC P. O. Box 62 Oak Ridge, Tennessee	1
ORA(RRRT) Holloman Air Force Base, New Mexico 88330	1	Oak Ridge National Laboratory ATTN: Central Files P. O. Box X Oak Ridge, Tennessee	1
Los Alamos Scientific Laboratory ATTN: Report Library P. O. Box 1663 Los Alamos, New Mexico 87544	1	Air Defense Agency, USACDC ATTN: Library Fort Bliss, Texas 79916	1
White Sands Missile Range ATTN: Technical Library White Sands, New Mexico 88002	1	U. S. Army Air Defense School ATTN: AKBAAS-DR-R Fort Bliss, Texas 79906	1
Rome Air Development Center (EMLAL-1) ATTN: Documents Library Griffiss Air Force Base, New York 13440	1		

	No. of Copies		No. of Copies
U. S. Army CDC Nuclear Group Fort Bliss, Texas 79916	1	<u>INTERNAL</u>	
Manned Spacecraft Center, NASA ATTN: Technical Library, Code BM6 Houston, Texas 77058	1	Headquarters U. S. Army Missile Command Redstone Arsenal, Alabama ATTN: AMSMI-D	1 1 1 1
Defense Documentation Center Cameron Station Alexandria, Virginia 22314	20	AMSMI-XE, Mr. Lowers AMSMI-XS, Dr. Carter AMSMI-Y AMSMI-R, Mr. McDaniel AMSMI-RAP	1 1 1 1 1
U. S. Army Research Office ATTN: STINFO Division 3045 Columbia Pike Arlington, Virginia 22204	1	AMSMI-RBLD USACDC-LnO AMSMI-RB, Mr. Croxton AMSMI-RBT	10 1 1 8
U. S. Naval Weapons Laboratory ATTN: Technical Library Dahlgren, Virginia 22448	1	National Aeronautics and Space Administration Marshall Space Flight Center Huntsville, Alabama ATTN: MS-T, Mr. Wiggins	5
U. S. Army Engineer Res. & Dev. Labs. ATTN: Scientific & Technical Info. Br. Fort Belvoir, Virginia 22060	2		
Langley Research Center, NASA ATTN: Library, MS-185 Hampton, Virginia 23365	1		
Research Analysis Corporation ATTN: Library McLean, Virginia 22101	1		
U. S. Army Tank Automotive Center ATTN: SMOTA-RTS.1 Warren, Michigan 48090	1		
Hughes Aircraft Company Electronic Properties Information Center Florence Ave. & Teale St. Culver City, California	1		
Atomics International, Div of NAA Liquid Metals Information Center P. O. Box 309 Canoga Park, California	1		
Foreign Technology Division ATTN: Library Wright-Patterson Air Force Base, Ohio 45400	1		
Clearinghouse for Federal Scientific and Technical Information U. S. Department of Commerce Springfield, Virginia 22151	1		
Foreign Science & Technology Center, USAMC ATTN: Mr. Shapiro Washington, D. C. 20315	3		

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author) Redstone Scientific Information Center Research and Development Directorate U.S. Army Missile Command Redstone Arsenal, Alabama 35809		2a. REPORT SECURITY CLASSIFICATION Unclassified
		2b. GROUP N/A
3. REPORT TITLE LIGHT REFLECTION FROM ROUGH SURFACES Optika i Spektroskopiya, 20, No. 4, 701-708 (1966)		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Translated from the Russian		
5. AUTHOR(S) (Last name, first name, initial) Polyanskiy, V. K. and Rvachev, V. P.		
6. REPORT DATE 15 September 1966	7a. TOTAL NO. OF PAGES 16	7b. NO. OF REFS 13
8a. CONTRACT OR GRANT NO. N/A	9a. ORIGINATOR'S REPORT NUMBER(S) RSIC-588	
b. PROJECT NO. N/A	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) AD _____	
c. _____		
d. _____		
10. AVAILABILITY/LIMITATION NOTICES Distribution of this document is unlimited.		
11. SUPPLEMENTARY NOTES None	12. SPONSORING MILITARY ACTIVITY Same as No. 1	
13. ABSTRACT The effect of the scattering of polarized light by a dull dielectric surface has been studied. The zeroth diffraction approximation proves to be more detailed than does the ray-optics approximation. In such an approximation, we must repeatedly explain the fact of light depolarization and the dependence of polarization effects upon the scattering conditions and also the displacement of the maximum of the scattering curve for larger observation angles. AUTHOR		

UNCLASSIFIED
Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Scattering properties Polarized light Dielectric surface Dull surfaces Light diffraction						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.